



KEY FEATURES


- Architectural Sliding window with external sliding sash.
- Clean lines for improved visual appearance.
- There is a large variety of window combinations possible (SF, FS, SFS, FSF or FSSF).
- The window is compatible with the high performance Series 406 FrontGLAZE™ and Series 407 FaceLINE™ framing.
- The head and jamb sections have an additional weather leg to ensure that junctions between sliders and fixed sidelights/highlights maintain the high water resistance.
- Sliders fitted with mortice lock.
- Sashes run on heavy duty double bogey wheel carriages.
- Threshold and snap-in flat filler ensure that the clean looks are maintained.




Standard splayed or alternative square rails.



Heavy duty double bogey wheel assembly standard.



Designed to go into commercial sub-sill.



Custom mortice lock is standard. Lock can be fitted with ICON™ stainless steel cover plate or ANDO™ powder coated cast aluminium cover.

GENERAL

Max Panel Height*
1600mm

Max Panel Width*
1500mm

Max Glass Thickness
24mm

Frame Depth
N/A

ENERGY

UW Range

SHGC Range

WEATHER

Maximum Water
600 Pa.

ACOUSTICS

This product has not been acoustics tested.



*Dimensions subject to individual site conditions.

elevatealuminium.com.au/701